

INVERTER (VISOKA A KLASA)

Diamond
Series

SRK-ZE

zidni tip



SRK63ZE-S1, SRK71ZE-S1




SRC63ZE-S1, SRC71ZE-S1



Mogućnosti



Duljina cjevovoda



SRK63ZE-S1, SRK71ZE-S1

Tehničke karakteristike

Model (Unut. jed./Vanjska jed.)			SRK63ZE-S1/SRC63ZE-S1	SRK71ZE-S1/SRC71ZE-S1
Izvor napona			Monofazni, 220-240V, 50Hz	
Kapacitet hlađenja	ISO-T1(JIS)	kW	6.3(0.9-7.1)	7.1(0.9-8.0)
Kapacitet grijanja	ISO-T1(JIS)	kW	7.1(0.9-9.0)	8.0(0.9-10.5)
Apsorbirana snaga (hlađ.)		kW	1.84(0.32-2.33)	2.21(0.32-2.98)
Apsorbirana snaga (grij.)		kW	1.86(0.26-2.62)	2.21(0.26-3.75)
Energetska klasa (hlađenje)			A	
Energetska klasa (grijanje)			A	
EER (kod hlađenja)			3.42	3.21
COP (kod grijanja)			3.82	3.62
Struja protjecanja (hlađenje)		A	8.4/8.1/7.7	10.1/9.7/9.3
Struja protjecanja (grijanje)		A	8.5/8.2/7.8	10.1/9.7/9.3
Zvučna snaga (u centru izvora buke)	Hlađenje(Unut./Vanj. jed.)	dB(A)	58/62	60/67
	Grijanje(Unut./Vanj. jed.)	dB(A)	59/63	60/64
Razina buke (na 1 metar od uređaja)	Hlađenje(Unut. jedinica)	dB(A)	Vi:43 Sr:39 Ni:33 SNI:26	Vi:45 Sr:40 Ni:34 SNI:26
	Grijanje(Unut. jedinica)	dB(A)	Vi:44 Sr:38 Ni:32 SNI:27	Vi:46 Sr:40 Ni:34 SNI:27
Vanjske dimenzije (vxšxD)	Unut. jed./Vanjska jed.	mm	381X1098X248/750X880X340	
Neto težina	Unut. jed./Vanjska jed.	kg	15/59	
Plinski cjevovod	Promjer cijevi	mm(in)	Tekuća faza: ϕ 6.35(1/4") Plinska faza: ϕ 15.88(5/8")	
	Metoda spajanja		Stezni spoj	
Rashladni medij			R410A	
Filter zraka	Antialergenski filter		x1	
	Fotokatalitički mirisni filter zraka		x1	